CONTEMPORARY DRINKING FOUNTAINS

GR Series

MODEL GRM45 BARRIER FREE. BI-LEVEL PEDESTAL MOUNTED DRINKING FOUNTAIN

STANDARD FEATURES

- Resistant to sunlight, heat, moisture and wear
- 18 gage, 304 stainless steel Bowl
- 12 gage, heavy duty stainless steel, corrosion and scratch resistant finish
- Polished Stainless Steel, Anti-Rotation Non-Squirt Bubbler

SUGGESTED SPECIFICATIONS

- 100-Mesh Inlet Strainer
- Access Door, heavy duty stainless steel, vandal resistant

Model GRM45 is a Barrier Free Pedestal Mounted, Vandal Resistant, Bi-Level Round Drinking Fountain made from 18 gage, 304 stainless steel Bowls mounted into a green powder coated 12 gage, heavy duty stainless steel Pedestal. Unit shall be activated by front mounted self-closing Buttons, by using less than 5 pounds of force, which activates internally mounted Valves with adjustable stream regulators controlling the water flow. Bubblers shall be polished stainless steel with non-squirt features and operate on water pressure range of 20 - 105 PSIG. Fountain is certified to ANSI A117.1, Public Law 111-380 (NO-LEAD), CHSC 116875 and NSF/ANSI 61, Section 9. Fixture meets ADA, ADA Standing Person, and ADA Child

Vandal resistant stainless steel Bottom Plate



MODEL: (Must Specify)

☐ GRM44 ☐ GRM45 ☐ GRM46	Satin stainless finish Green powder-coated (Shown) Red powder-coated
GRM47 Blue powder-coated Custom color finishes available upon request	

Custom color finishes available upon request				
OPTIONS (additional costs may be incurred)				
☐ -CH30 ☐ -FRU2 ☐ -FRU3 ☐ -FRU4 ☐ -FS ☐ -HB1	Child height, 30" Bubbler height Freeze resistant, 2 Valves ¹ Freeze resistant, 3 Valves ¹ Freeze resistant, 4 Valves ¹ Foot Shower Hose Bibb, compression, with hose threaded outlet/VB			
☐ -HB3 ☐ -IAP ☐ -IGM ☐ -JF1 ☐ -JF2 ☐ -JFFR1	Hose Bibb, loose key, vandal resistant, locked door with hose threaded outlet/VB ^{1 2} In-ground Anchor Plate In-ground 14" Mounting Adapter Jug Filler, Spigot, self-closing Valve with Plain End ^{1 2} Jug Filler, Pushbutton, self-closing Valve w/ Plain end ¹ Jug Filler, Pushbutton, Freeze Resistant, self-closing Valve ¹			
□ -NP2	Non-Pollutable, Freeze Resistant, 2 Valves			

Non-Pollutable, Freeze Resistant, 3 Valves



See separate option sheet.

² This option is not available freeze-resistant.

requirements when mounted appropriately.

with the









□I -NP3

Water Conservina Product

Pet Fountain Receptor 1

MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • www.murdockmfg.com



Revised: 09/27/2023



CONTEMPORARY DRINKING FOUNTAINS SINCE 1853

IMPORTANT: INSTALLATION AND SITE PREP FOR FREEZE RESISTANT OPTIONS "-FRU, -NP" WILL DIFFER FROM STANDARD. REFER TO DESIGNATED FREEZE RESISTANT INSTALLATION DETAILS.

 \odot

30" [762]

-12" [305] -

8³/₈" [213]

33"

[839]

6" [152]

GR Series

MODEL GRM45 BARRIER FREE. BI-LEVEL PEDESTAL MOUNTED DRINKING FOUNTAIN

Valve specifications: Minimum/Maximum Pressure 30 to 100 PSI.

Combined Waste

Bottom Access


Supplied Anchors

Outlet

Panel

Back Access

Panel



OPTIONAL -PF PET FOUNTAIN DETAIL

General Notes:

- 1. All dimensions are in inches [mm].
- *2. Standard adult ADA height model shown. Optional -CH30 child ADA height model available.
- 3. Stop Valve not provided.

		— Supplied Alichors	
			_
SELECTION SUMMARY & APPROVAL FOR MANUFACTURING			All
M P N	Model Number & Options		mi
2 A E	Company		ch as
202 202	Company		 VC
등유교	Contact	Title	ma op
A P E	Signature		Me Int
ᅜᇓᆇᆯ	Signature (Approval for Manufacturing)	5.	w
~~	manutacturing)	Date	 си

ll dimensions are subject to anufactures tolerance of plus or inus 1/4" nominal and subject to nange without notice. Murdock® ssumes no responsibility for use of oid or superseded data. Dimensions hay change with the addition of otional accessories. Murdock® Mfg. lember of Morris Group nternational®. Please visit www.murdockmfg.com for most

current specifications

Member of MORRIS GROUP