

XT Series 10 and 12 Foot Extra Heavy Duty Rectangular Tables with Lumber Top and Seats

SPECIFICATION BULLETIN
#SPC-TB-153

REV. 11-08



Model XT/G-10UP 10 Ft. Extra Heavy Duty Portable Rectangular Table with Hot Dip Galvanized Frames and Untreated Southern Yellow Pine Top and Seats

- Constructed specifically for heavy use areas
- Nontip, nontrip walk-through design
- All welded end frames are fabricated from 2-3/8" diameter steel pipe
- Die-formed center channel and diagonal braces align and strengthen entire table
- Frames are hot dip galvanized after fabrication for superior corrosion resistance
- Precision drilled, Untreated #1 Southern Yellow Pine top and seat planks
- Limited lifetime warranty on frames

SPECIFICATIONS:

- •XT Series end frames are one-piece welded construction, fabricated from 2.375" (2-3/8") O.D. steel pipe to meet 2" nominal steel pipe size specifications with 2" x 2" x 3/16" A-36 structural grade steel angle for attaching the seats and top.
- Table frame design incorporates nontip, nontrip, walk-through design features. Bends are tightly formed to prevent tipping when weight is on one side.
- Model XT/G-10UP is a nominal 10 ft. long with three frames.
- Model XT/G-12UP is a nominal 12 ft. long with three frames.
- Nominal table height is 30". Nominal seat height is 18".
- Frames are supported by diagonal braces of 1-5/16" O.D. x 14 ga. wall steel pipe that connect to a die-formed steel channel designed to align and provide attachment to the table top.
- **Standard:** All frame components are be hot-dip galvanized after fabrication to ASTM-A123 to maintain an average zinc coating of 2.0 oz. per sq. ft. of surface area (indicated by "/G" in model no.), e.g. XT/G-10UP.
- All galvanized fasteners are provided for assembly.
- •Standard: Lumber is Untreated #1 grade Southern Yellow Pine (indicated by "UP" in model no., e.g. XT/G-10UP) 2" x 10" nominal sized planks, kiln dried to reduce moisture content. All lumber is precision drilled to facilitate assembly and has all exposed edges removed to a 3/8" radius.
- **Optional:** Color choices of powder coated steel frame components. See Specification Bulletin #SPC-CO-001.
- Optional: Treated #1 Southern Yellow Pine is readily available and is pressure treated (KDAT) to preserve wood against decay. To specify, change "UP" in model no. to "TP", e.g. UT/G-10TP. (Cedar, Fir and Redwood are available when in stock —please inquire.)

AVAILABLE OPTIONS

10' or 12' length

Choice of colors of Powder Coated finish for steel frame components

Pressure treated #1 Southern Yellow Pine lumber (Cedar, Fir, or Redwood lumber when in stock)

